

DESCRIPTION

INDUSTRIAL ROBOT

TECHNICAL FIELD

The present invention relates to an industrial robot used for welding, for example, and used in floor-mounted or a ceiling-mounted installation.

BACKGROUND ART

Conventionally, as an installing and using method of a welding multi-joint robot (an industrial robot), floor-mounted use, ceiling-mounted use, or the like, is generally known. Fig. 6 is a perspective view showing such an industrial robot when it is used in a state in which it is mounted on a floor. Fig. 7 is a side view showing such an industrial robot when it is used in a state in which it is mounted on a ceiling.

First arm 112 rotates with respect to base 111 for installation. Second arm 113 pivots with respect to first arm 112, and third arm 114 pivots with respect to second arm 113. Furthermore, fourth arm 115 pivots with respect to third arm 114. Welding wire feeder 116 feeds a welding wire. Fixing device 117 fixes welding wire feeder 116 to the industrial robot. Torch cable 118 feeds the welding wire from welding wire feeder 116 to welding torch 119.

In Fig. 6, welding wire feeder 116 is fixed to the upper part of third arm 114. Such a configuration is disclosed in, for example, Japanese Patent Unexamined Publication No. 2004-261878. Furthermore, in Fig. 7, welding wire feeder 116 is fixed to the side face of third arm 114. Such a configuration is disclosed in, for example, Japanese Patent Unexamined Publication No. H8-57648. Thus, in a conventional welding multi-joint robot, the position to which welding wire feeder 116 is attached is different between the time of floor-

mounted use and the time of ceiling-mounted use. That is to say, the structure (specification) is generally different between the floor-mounted use and the ceiling-mounted use.

Therefore, when a robot used in a state in which it is mounted on the floor is used in a state in which it is mounted on the ceiling, or when a robot used in a state in which it is mounted on a ceiling is used in a state in which it is mounted on a floor, the position to which welding wire feeder 116 is attached has to be changed. In order to correspond to such a change, it is necessary to provide fixing positions of wire feeder 116 for both floor-mounted use and ceiling-mounted use. That is to say, two or more positions to which wire feeder 116 is attached need to be provided. Furthermore, it is necessary to prepare attaching members for fixing welding wire feeder 116 corresponding to each use form of floor-mounted use and ceiling-mounted use. Thus, it takes a time to change the use forms, and the cost therefor rises.

Furthermore, in coupling of a feeder cable for electrically coupling between welding wire feeder 116 and the inside the robot, it is necessary to additionally consider a wiring method corresponding to each use form. Thus, it takes a time to change the coupling corresponding to the use form.

Furthermore, in the structure shown in Fig. 7, welding wire feeder 116 is attached to the side face of third arm 114. Therefore, the distance between a location of the center of gravity of welding wire feeder 116 and the industrial robot (the arm) is increased, and a moment load to fixing device 117 for attaching welding wire feeder 116 is increased.

In order to resist this load, the strength and rigidity of fixing device 117 is required to be increased. That is to say, the size and mass of a member constituting fixing device 117 may be increased. Such a configuration deteriorates the motion performance of the industrial robot and adversely

affects the approaching performance to a welding work and a jig for fixing the welding work.

SUMMARY OF THE INVENTION

An industrial robot of the present invention includes a base for
5 installation, a first arm, a second arm, a third arm, a wire feeder, a welding torch, and a torch cable. The first arm rotates with respect to the base. The second arm pivots with respect to the first arm. The third arm pivots with respect to the second arm. The torch cable is coupled to the wire feeder and feeds a welding wire to the welding torch. The wire feeder is provided to the
10 second arm and is rotatable around a rotation axis. In this structure, a position in which the wire feeder is provided is common in a robot used in a state in which it is mounted on a floor and a robot used in a state in which it is mounted on a ceiling. Then, by rotating the wire feeder, floor-mounted use and ceiling-mounted use become possible.

15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a side view showing a state of an industrial robot at the time of floor-mounted installation in accordance with an exemplary embodiment of the present invention.

Fig. 2 is a side view showing a state of the industrial robot at the time of
20 ceiling-mounted installation in accordance with the exemplary embodiment of the present invention.

Fig. 3 is a partial sectional view showing a vicinity of a fixing device for a welding wire feeder of the industrial robot in accordance with the exemplary embodiment of the present invention.

25 Fig. 4 shows a state in which a rotation angle of the welding wire feeder of the industrial robot is fixed by the fixing device in accordance with the exemplary embodiment of the present invention.

Fig. 5 is a top view showing the industrial robot in accordance with the exemplary embodiment of the present invention.

Fig. 6 is a perspective view showing a state of a conventional industrial robot at the time of floor-mounted installation.

5 Fig. 7 is a side view showing a state of a conventional industrial robot at the time of ceiling-mounted installation.

REFERENCE MARKS IN THE DRAWINGS

- 11 base
- 12 first arm
- 10 13 fourth arm
- 14 second arm
- 15 third arm
- 16 welding wire feeder
- 17 fixing device
- 15 17A rotation axis
- 18 torch cable
- 19 welding torch
- 21 rotating hollow pipe shaft
- 22 feeder cable
- 20 31 rotation fixing part
- 111 base
- 112 first arm
- 113 second arm
- 114 third arm
- 25 115 fourth arm
- 116 welding wire feeder
- 117 fixing device

118 torch cable

119 welding torch

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT
(FIRST EXEMPLARY EMBODIMENT)

5 Fig. 1 is a side view showing an industrial robot in a state in which it is mounted on a floor in accordance with the present exemplary embodiment. Fig. 2 is a side view showing the industrial robot in a state in which it is mounted on a ceiling. In the following description, the direction of an industrial robot seen from a floor surface or a ceiling surface is defined as an
10 upper side.

 Base 11 is provided to install the industrial robot on a floor surface, a ceiling surface, or the like. First arm 12 rotates with respect to base 11. Fourth arm 13 pivots with respect to first arm 12, and second arm 14 pivots with respect to fourth arm 13. That is to say, second arm 14 pivots with
15 respect to first arm 12. Third arm 15 pivots with respect to second arm 14. Welding wire feeder (hereinafter, referred to as "feeder") 16 is provided at the upper side of second arm 14. Torch cable 18 feeds a welding wire from feeder 16 to welding torch 19.

 Fixing device 17 is provided to attach feeder 16 to second arm 14.
20 Fixing device 17, which has rotation axis 17A for allowing feeder 16 to turn, rotatably fixes feeder 16 and fixes the rotation angle of feeder 16. Thus, fixing device 17 fixes feeder 16 at a position in which feeder 16 is offset in the horizontal direction to a degree in which torch cable 18 attached to feeder 16 does not interfere with third arm 15. That is to say, feeder 16 is provided to
25 second arm 14 and can rotate around rotation axis 17A.

 Fourth arm 13 is attached like a cantilever to first arm 12 and second arm 14. That is to say, fourth arm 13 is attached to one side face of first arm

12 and to one side face of second arm 14. Feeder 16 is located on the opposite side to fourth arm 13 relatively to a rotating axis (not shown) of first arm 12. The rotating axis of first arm 12 is an axis for rotatably attaching a first arm 12 to base 11.

5 If feeder 16 is attached to the same side as fourth arm 13 relatively to the rotating axis of first arm 12, when second arm 14 pivots, feeder 16 interferes with fourth arm 13. Therefore, the operation range of second arm 14 is restricted. Furthermore, in order to avoid the interference of feeder 16 to fourth arm 13, the position to which feeder 16 is attached is required to be offset
10 to the outside of fourth arm 13. This structure leads to increase in the size and weight of fixing device 17, resulting in deterioration of the motion performance and approaching performance to a welding work, etc. in an industrial robot.

 When feeder 16 is attached to the opposite side to fourth arm 13 relatively to the rotating axis of first arm 12, problems associated with
15 interference mentioned above or unnecessary increase in the size and weight of fixing device 17 do not arise. Therefore, deterioration of the motion performance and approaching performance to a welding work, etc. in an industrial robot can be prevented.

 Fig. 3 is a partial sectional view showing a vicinity of fixing device 17.
20 Rotating hollow pipe shaft (hereinafter, referred to as "shaft") 21 is provided to fixing device 17 and is located on the rotation center of the fixing device 17 to constitute rotation axis 17A. Feeder cable (hereinafter, referred to as "cable") 22 electrically couples feeder 16 to the inside of the industrial robot. Cable 22 is wired through the inside of shaft 21.

25 Fig. 4 is a perspective view showing a state in which a rotation angle of feeder 16 is fixed by fixing device 17 at the time of floor-mounted use shown in Fig. 1. In this case, feeder 16 is fixed facing upward. Note here that rotation

fixing portion 31 that is a part of fixing device 17 fixes feeder 16 at a predetermined angle.

Fig. 5 partially shows a state in which feeder 16 is fixed on second arm 14 at the time of floor-mounted use shown in Fig. 1, which is seen from the upper side of the industrial robot to the side of a floor surface. Location of gravity center 41 of schematically represents a location of the center of gravity of feeder 16.

Next, in the industrial robot having the above-mentioned configuration, the use form of the industrial robot is described as to the case in which floor-mounted use shown in Fig. 1 is changed to the ceiling-mounted use shown in Fig. 2 as an example. Firstly, the industrial robot is fixed to a ceiling surface (not shown) by using base 11. Next, feeder 16 is rotated around rotation axis 17A of fixing device 17 from the state shown in Fig. 1 to the state shown in Fig. 2 and fixed. That is to say, feeder 16 is fixed facing downward (to the side of the ceiling). Next, third arm 15 is rotated by 180° into a posture shown in Fig. 2, the industrial robot is made in a state capable of welding a work (not shown) located at the side of a floor surface (not shown), for example.

Thus, fixing device 17 for fixing feeder 16 to second arm 14 can be commonly used at the time of floor-mounted use and the time of ceiling-mounted use. That is to say, it is not necessary that fixing devices are provided independently at the time of the floor-mounted use and the time of ceiling-mounted use. Furthermore, the position to which the fixing device is attached is common and the position is not required to be changed.

Furthermore, fixing device 17 is provided with rotation axis 17A that allows feeder 16 to rotate. Then, according to whether floor-mounted installation or ceiling-mounted installation, feeder 16 is allowed to rotate around rotation axis 17A. Thus, by changing an angle of feeder 16, the

position of torch cable 18 can be changed into the direction suitable for the time of the floor-mounted use and ceiling-mounted use. That is to say, an attachment angle of feeder 16 is changed by rotating feeder 16 without changing the position to which feeder 16 is attached between the time of floor-mounted use and the time of ceiling-mounted use. Since only this configuration can correspond to both the floor-mounted use and ceiling-mounted use of an industrial robot, an industrial robot with excellent workability can be obtained.

Note here that depending on a method of carrying out welding and a shape of a welding base material, and the like, torch cable 18 may be required to be fixed in order to restrict the interference range of torch cable 18. In such a case, by using rotation fixing part 31, a bolt, or the like, shown in Fig. 4, feeder 16 can be fixed at an angle necessary to avoid interference of torch cable 18.

Furthermore, as shown in Figs. 3 and 4, cable 22 passes through the inside of shaft 21. With such a structure, even when feeder 16 is rotated, layout of cable 22 inside shaft 21 constituting rotation axis 17A is not affected. That is to say, when an industrial robot is changed from the floor-mounted use to the ceiling-mounted use, or when an industrial robot is changed from the ceiling-mounted use to the floor-mounted use, it is not necessary to change layout or coupling of cable 22. Therefore, workability associated with the change between the floor-mounted use and the ceiling-mounted use of the industrial robot can be improved.

Furthermore, as shown in Fig. 5, in order to allow feeder 16 to rotate, it is preferable that a position to which feeder 16 is attached is offset to a position apart from third arm 15. At this time, offsetting is carried out at minimum to a degree in which torch cable 18 attached to feeder 16 does not interfere with

second arm 14 and third arm 15. With this attachment position, the distance between location of the gravity center 41 of feeder 16 and a pivot axis of third arm 15 is reduced. Therefore, a moment load applied to fixing device 17 for fixing feeder 16 to second arm 14 becomes small. Note here that, the shorter
5 the distance between the location of the gravity center 41 and the pivot axis of third arm 15 is, the smaller the moment load becomes. Therefore, it is desirable that at least a part of feeder 16 is located on second arm 14.

As mentioned above, with the configuration in which the distance between location of the gravity center 41 and the pivot axis of third arm 15 is
10 short, a strong attachment member for attaching feeder 16 is not required to be provided. Thus, the industrial robot can have a compact size and light weight.

Note here that, in this exemplary embodiment, fourth arm 13 is pivotably provided between first arm 12 and second arm 14. However, feeder 16 may be provided on second arm 14 in an industrial robot that does not have
15 fourth arm 13.

INDUSTRIAL APPLICABILITY

An industrial robot of the present invention can be used both at the time of floor-mounted use and ceiling-mounted use. Therefore, it is useful as an industrial robot capable of carrying out welding and the like, by mounted on
20 a floor, on a ceiling, or the like.